

**Rundschalldämpfer - Einfügungsdämmwerte im Kanal
Cylindrical Attenuator - In duct insertion losses**

f ₁	f ₂	0	1	2	3	8	9	8	7
300	CA-1D	0	1	2	3	8	9	8	7
	CA-2D	0	2	4	6	12	13	12	11
	CPA-1D	1	5	7	14	19	16	13	12
	CPA-2D	3	8	14	20	25	22	20	19
350,400	CA-1D	0	1	2	4	9	9	7	7
	CA-2D	0	2	4	8	13	13	11	10
	CPA-1D	1	5	7	16	20	17	13	12
	CPA-2D	4	8	15	20	25	23	19	17
450,500	CA-1D	0	1	2	6	9	9	7	7
	CA-2D	0	2	3	10	13	13	11	10
	CPA-1D	2	6	10	18	22	20	14	13
	CPA-2D	5	10	15	21	26	24	22	19
550,600	CA-1D	0	1	3	7	9	8	6	6
	CA-2D	0	2	5	12	13	12	9	9
	CPA-1D	2	6	11	18	23	21	15	14
	CPA-2D	5	10	16	23	26	25	24	19
650,700	CA-1D	0	1	3	8	8	7	5	4
	CA-2D	0	2	6	13	13	11	8	7
	CPA-1D	3	6	12	18	23	21	15	13
	CPA-2D	5	11	22	23	26	25	22	17
800,1000	CA-1D	0	2	4	8	8	6	4	3
	CA-2D	1	3	8	13	13	10	7	6
	CPA-1D	3	6	12	20	24	19	13	12
	CPA-2D	5	12	17	26	27	26	21	15
1200	CA-1D	0	2	6	8	7	5	3	3
	CA-2D	1	4	10	13	12	7	5	5
	CPA-1D	3	6	13	21	23	14	10	9
	CPA-2D	6	12	19	26	27	20	16	13
1600	CA-1D	1	3	7	8	6	5	3	3
	CA-2D	2	6	12	13	11	7	5	4
	CPA-1D	4	7	14	20	22	12	8	8
	CPA-2D	6	13	22	25	27	25	12	10
1800	CA-1D	1	4	7	8	6	4	3	3
	CA-2D	2	7	12	13	11	7	5	4
	CPA-1D	4	8	15	18	20	10	6	6
	CPA-2D	7	13	22	25	27	25	10	8